



## Cat 6 UTP Keystone Jacks



### Cat 6 UTP Keystone Jacks 90 degree & 180 degree

#### Product Description

Horizontal style Cat6 90 degree keystone jacks for Faceplate, 180 Degree for unloaded Patch Panel it features dual color-coded wiring label with both T568A/B wiring pattern.

Rear termination field for easy termination of a jack while installed in a wall plate, surface mount boxes and blank patch panels for a wide of applications.

#### Features and benefits

- Available in Cat6 T568A/B wiring schemes, meet or exceed TIA/EIA Cat6 requirements
- The new design allows high density solution
- The V style IDC contacts flex not fatigue when terminated
- Termination caps prevent wire from dropping off
- Housing: high temperature thermoplastic
- Compact jack design, 8 positions and 8 conductors
- Contact: phosphor bronze , phosphor bronze with 6 to 50 u" gold plate
- Accept 22-26 AWG solid with a insulation diameter of 0.4 - 0.6 mm
- Easy to be terminated Low attenuation loss and high return loss
- High reliability and superior performance
- Available in different colors

Part number	Description	Carton	Carton measurement	Weight
	Cat 6 UTP keystone jack, 90°	250 pcs	53.5cm x 31.3cm x 23.4cm	4.2 KG
	Cat 6 UTP keystone jack with cover, 90°	250 pcs	53.5cm x 31.3cm x 23.4cm	4.2 KG
	Cat 6 UTP keystone jack, 180°	250 pcs	53.5cm x 31.3cm x 23.4cm	4.2 KG